

# 9415<sup>NEW</sup>

## 9415 LED Lantern



### Overview

#### 9410L + SAFETY=9415

Everything that's great about the 9410L LED Lantern, plus safety approvals

At just 3 pounds and 413\* lumens, the new 9415 LED Lantern packs the power without the weight. Four LEDs, powered by the latest generation Ni-MH batteries illuminate a distance of 360 yards (325\* meters). And it's loaded with innovative technology and features you have come to expect from Pelican:

- Approvals: Class I Div. 1 Groups ABCD T4
- 120° rotating head
- Run time\*: 12h (low)/4h 30m (high)
- Battery status indicator
- 3 mode switch (high, low, flashing)

- Shoulder strap included

Safety approved for the most volatile work areas, the 9415 LED Lantern is safe and one of the most compact, high output lanterns on the market.

### 9415 LED Lantern:

Lightweight, big LED performance you can trust.

\*Performance data is to FL 1 standards

**Body:** ABS

**Lens:** Polycarbonate

**Shroud:** EXL

**Switch Type:** Push button multi-functional switch- high, low, & flashing

**Modes:** High/Low/Flashing

**O-Ring:** EPDM gasket

Minimum Pack 1 ea.

### COLORS




### CONFIGURATIONS

Cat. #	Description
9415	9415 LED Lantern (Boxed)

### Specs

#### APPROVALS

---

 Class I, Div. 1 Groups ABCD T4

---

IPX4 = Water Resistant

IPX7 = Water Proof (submerged to 1 meter for 30 min.)

IPX8 = Submersible (submerged to 100 meters for 4 hours)

#### ACCESSORIES

**6057F 110V Transformer for Fast Charger**



---

**6061F Direct Wiring Rig for Fast Charger**





**8056F 12V Plug-in for Fast Charger**



**9413DL Diffuser Lens for 9410/9415**

**9416 Desk/Dash Fast Charger Base Unit**

**9418 NiMh Div 1 Replacement Battery Pack**

Accessories shown are for reference only, and are subject to change at manufacturers discretion.

#### **SIMILAR PRODUCTS**



**9410L LED Lantern**

800.473.5422

All trademarks are registered and/or unregistered trademarks of Pelican Products, Inc., its subsidiaries and/or affiliates.

© 2014 Pelican Products, Inc.